

Tile Drill Bits **KERAMIK** by

for **ceramic, porcelain & granite tiles**

USAGE



**CERAMICS
PORCELAIN
GRANITE**



**TILES
HARD BURNT BRICK**

- ▲ DIN 8039 / ISO 5468
- ▲ Asymetric spiral shape
- ▲ Cutting drilling spiral for optimum spoil removal
- ▲ Straight flute entry
- ▲ Tungsten-titanium tip
- ▲ High-temperature brazing at about 1,120°C
- ▲ Burnished surface



The **KERAMIK** has an extremely hard and sharp carbide tip, diamond ground from Tungsten-Titanium, with a **hardness grade of 9, which has never been used before!**

Low stress high temperature brazing prevents detaching of carbide tip when drilling extremely dense materials under most extreme loads.

Depending of the hardness and density of the tile, the **KERAMIK** drill bit will last from 10 to approx. 100 drill holes.

KERAMIK comes in a set of 5 Drill bits size 5/32" to 3/8"

APPLICATION

- ▲ in all rotary and percussion drilling machines
- ▲ High Contact pressure
- ▲ 20 seconds cooling time
- ▲ Only for rotary use
- ▲ Speed 1,500 to 2,000 rpm

TILE EZE

SOUTHWEST EQUIPMENT MANAGEMENT, INC.

Pioneering equipment for the tile & marble trades

TILE EZE · P.O. Box 111390 · NAPLES, FLORIDA 34108-0124
PH. 239-598-3737 · TOLL FREE 1-800-476-3737 · FAX 239-597-5961

E-MAIL: TILEEZE@AOL.COM · WEBSITE: WWW.TILE-EZE.COM